

Please type a plus sign (+) inside this box →

+

06-15-00

A

PTO/SB/05 (12/97)

Approved for use through 09/30/00. OMB 0651-0032

Patent and Trademark Office U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.

MICS:0053

Total Pages

69

First Named Inventor or Application Identifier

Willard Lloyd Hofer

Express Mail Label No.

EL 432942885-US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:

Assistant Commissioner for Patents

Box Patent Application

Washington, DC 20231

1. ☒ Fee Transmittal Form
(Submit an original, and a duplicate for fee processing)
2. ☒ Specification Total Pages 26
(preferred arrangement set forth below)
 - Descriptive
 - Cross References to Related Application
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 USC 113) Total Sheets 11
Total Pages 33
4. Oath or Declaration
 - a. ☒ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37CFR 1.63(d))
(for continuation/divisional with Box 17 completed)
[Note Box 5 below]
 - i. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b)
5. ☐ Incorporation By Reference (useable if Box 4b is checked)
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein

6. ☐ Microfiche Computer Program (Appendix)
7. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet & document(s))
9. ☒ 37 CFR 3.73(b) Statement ☐ Power of Attorney
(where there is an assignee)
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)
14. ☐ Small Entity ☐ Statement filed in prior application
Statement(s) Status still proper and desired
15. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
16. ☐ Other

17. ☐ Continuation

☐ Divisional

☐ Continuation-in-part (CIP) of prior application No _____/_____

18. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label

☒ Correspondence address below

(Insert Customer No. or Attach bar code label here)

NAME Michael G. Fletcher
Fletcher, Yoder & Van Someren

ADDRESS P.O. Box 692289

CITY Houston

STATE

Texas

ZIP CODE

77269-2289

COUNTRY USA

TELEPHONE

(281) 970-4545

Fax

(281) 970-4503

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

United States Patent Application For

ROTATING GRIPPER WAFER FLIPPER


BY:

WILLARD LLOYD HOFER
469 S. EMILY
BOISE, IDAHO 83709

SHAWN DANIEL DAVIS
3023 W. VAL VISTA CT.
MERIDIEN, IDAHO 83642

AND

JOE LEE PHILLIPS
2903 BOBCAT DRIVE
NAMPA, IDAHO 83687

"EXPRESS MAIL" MAILING LABEL	
Number:	<u>EL 432 942 885 US</u>
Date of Deposit:	<u>June 14, 2000</u>
<i>Pursuant to 37 C.F.R. § 1.10, I hereby certify that I am personally depositing this paper or fee with the U.S. Postal Service, "Express Mail Post Office to Addressee" service on the date indicated above in a sealed envelope (a) having the above-numbered Express Mail label and sufficient postage affixed, and (b) addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.</i>	
Signature:	
Printed Name	<u>Jennifer Presswood</u>

ROTATING GRIPPER WAFER FLIPPER

BACKGROUND OF THE INVENTION

5 1. Field Of The Invention

The present invention relates generally to integrated circuit fabrication and, more particularly, to the inspection of semiconductor wafers.

2. Background Of The Related Art

10 This section is intended to introduce the reader to various aspects of art which may be related to various aspects of the present invention which are described and/or claimed below. This discussion is believed to be helpful in providing the reader with background information to facilitate a better understanding of the various aspects of the present invention. Accordingly, it should be understood that these statements are to be read in this light, and not as admissions of
15 prior art.

Integrated circuits are generally mass produced by fabricating thousands of identical circuit patterns on a single semiconductor wafer and subsequently dividing them into identical die or chips. Semiconductor wafers are generally made of silicon. To produce the
20 integrated circuit, many commonly known processes are used to modify, remove, and deposit material onto the semiconductor wafer. Processes such as ion implantation, sputtering, etching, chemical vapor deposition and variations thereof are among those processes commonly used. These processes are often selectively applied to an integrated circuit through the use of a masking process. In the masking process, a photomask containing the

pattern of the structure to be fabricated is created, and the wafer is coated with a photolithographic material, generally a photoresist. Next, the resist-coated wafer is exposed to ultraviolet light through a photomask to soften or harden parts of the resist, depending on whether a positive or negative photoresist is used. Once the softened parts of the photoresist are removed, the wafer is treated by one of the processes discussed above to modify, remove, or replace the part unprotected by the photoresist, and then the remaining photoresist is stripped from the semiconductor wafer. The masking process permits specific areas of the integrated circuit to be modified, removed, or replaced.

10 An integrated circuit device is built in three major steps of the wafer fabrication process. In the first step, the active and passive parts are fabricated in and on the wafer surface. The last step comprises a series of steps which are used to cover the completed chip surface with a protective layer. The step in between consists of the processes that put one or more layers of conducting metal on the wafer surface and the patterning process that leaves the circuit components electrically connected.

15 Once the integrated circuit has been built on the silicon wafer, the wafer is evaluated and electrically tested to determine which integrated circuit die are good so that they may be packaged for use. One of the fundamental methods of evaluating the semiconductor wafer is to inspect the wafer optically for any visible anomalies. By physically inspecting the wafer surface, an operator may detect processing pattern flaws or isolated anomalies which may be corrected to increase the yield of usable integrated circuit die on the semiconductor wafer.

Inspection stations containing a surface to hold the wafer, magnifying devices, and lights are common in the wafer manufacturing process.

Traditionally, a semiconductor wafer is placed in a wafer carrier, such as a wafer boat or wafer cassette. At various points in the processing, the wafers are physically removed from the wafer carrier by an operator and placed on an inspection device. Often times, the wafer must be manually rotated to inspect the entire wafer adequately. Next, the wafer is either flipped so that the backside may be inspected at the same workstation, or the wafer may be transferred to another inspection station to inspect the backside of the wafer. Either way, there is more physical handling of the wafer by operators. Each time the wafer is physically handled by an operator, the chances of damaging the wafer increase. Semiconductor wafers are often chipped, cracked, scratched, or broken due to operator handling errors. Unfortunately, conventional inspection of the semiconductor wafer necessitates the physical handling of the semiconductor wafer to manipulate the wafer to examine all areas and both sides of the wafer. What is needed is an inspection device which will allow an operator to inspect all areas and both sides of the wafer with minimal handling of the wafer.

The present invention may address one or more of the problems set forth above.

SUMMARY OF THE INVENTION

Certain aspects commensurate in scope with the originally claimed invention are set forth below. It should be understood that these aspects are presented merely to provide the

reader with a brief summary of certain forms the invention might take and that these aspects are not intended to limit the scope of the invention. Indeed, the invention may encompass a variety of aspects that may not be set forth below.

5 In accordance with one aspect of the present invention, there is provided an apparatus for inspecting a disc-like substrate. The apparatus includes a holding structure having members arranged to hold and rotate the substrate about a first axis. The holding structure is connected to a rotatable member which is configured to rotate the holding structure about a second axis different from the first axis.

10

 In accordance with another aspect of the present invention, there is provided a method of inspecting a semiconductor wafer comprising the acts of: loading the substrate into a holding structure, the substrate having a first surface and a second surface; inspecting the first surface of the substrate by rotating the substrate within the holding structure about a first axis, the first axis disposed generally perpendicular to the surface of the substrate and extending generally through the axial center of the substrate; rotating the holding structure about a rotatable member to rotate the substrate approximately 180° about a second axis, the rotatable member being mechanically coupled to the holding structure; inspecting the second surface of the substrate; and removing the substrate from the holding structure.

15

20

 In accordance with yet another aspect of the present invention, there is provided a method of fabricating an integrated circuit package comprising the acts of: disposing a plurality of integrated circuit devices onto a silicon wafer; inspecting the wafer by: loading

the wafer into a wafer holding structure, the wafer having a first surface and a second surface; inspecting the first surface of the wafer by rotating the wafer within the wafer holding structure about a first axis, the first axis disposed generally perpendicular to the surface of the wafer and extending generally through the axial center of the wafer; rotating the wafer holding structure about a rotatable member to rotate the wafer approximately 180° about a second axis, the rotatable member being mechanically coupled to the wafer holding structure; inspecting the second surface of the wafer; and removing the wafer from the wafer holding structure; electrically testing the integrated circuit devices; singulating the integrated circuit devices; and packaging selected singulated integrated circuit to form respective integrated circuit packages.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing and other advantages of the invention will become apparent upon reading the following detailed description and upon reference to the drawings in which:

Fig. 1 illustrates an exemplary process flow for building an I/C device;

Fig. 2 illustrates a perspective view of a rotating gripper wafer flipper;

Fig. 3 illustrates a perspective view of the rotating gripper wafer flipper illustrated in Fig. 2 with a semiconductor wafer loaded in the gripper arms and illustrating the rotational axis';

Fig. 4 illustrates one embodiment of a motor assembly in accordance with the present invention;

Figs. 5A, 5B and 5C illustrate a flipping sequence;

5

Fig. 6 illustrates a perspective view of the wafer holding structure according to one embodiment of the present invention;

10

Fig. 6A illustrates a cross-sectional view of the wedge assembly illustrated in fig. 6;

Fig. 7 illustrates a partial cross-section of the perspective view of the rotating gripper wafer flipper illustrated in Fig. 1, taken along line 5-5; and

15

Fig. 8 illustrates a flow chart of an inspection process according to the present invention.

DESCRIPTION OF SPECIFIC EMBODIMENTS

One or more specific embodiments of the present invention will be described below.

20

In an effort to provide a concise description of these embodiments, not all features of an actual implementation may be described in the specification. It should be appreciated that in the development of any such actual implementation, as in any engineering or design project, numerous implementation-specific decisions must be made to achieve the developers' specific goals, such as compliance with system-related and business-related constraints,

which may vary from one implementation to another. Moreover, it should be appreciated that such a development effort might be complex and time consuming, but would nevertheless be a routine undertaking of design, fabrication, and manufacture for those of ordinary skill having the benefit of this disclosure.

5

An integrated circuit device is generally built on a wafer following a flow similar to that illustrated in Fig. 1. First, a substrate material, such as silicon, is provided for wafer fabrication (block 11). Wafer fabrication generally includes the fabrication of active and passive parts on the wafer surface and the deposition of one or more layers of conductive material which is patterned to electrically connect all of the active circuit components. The wafer is then generally covered with a protective material such as a polyamide. Next, the frontside, backside, and edges of the wafer may be inspected visually (block 12). Advantageously, the present invention may facilitate an optimal method for inspecting the wafer. Generally, wafer inspection is performed by human operators. However, the present invention may be useful in conjunction with an optical sensor, which may be used to inspect a wafer without human operators. During wafer inspection, the wafer is inspected for visual anomalies (block 13). If there are no visual failures, the wafer may be tested for electrical failures (block 14). The good integrated circuit devices may then be singulated, commonly by a saw process, and then packaged for use in a system (block 15). If there are visual failures at inspection, it is determined whether the wafer may be re-workable (block 16). If the anomaly is not re-workable, the wafer is generally scrapped (block 17). If it is determined that the wafer may be re-workable, the wafer is generally sent to be re-worked to

correct the anomaly (block 18). Once the wafer is re-worked, it may be sent back for visual inspection (block 12) once again.

The present embodiment may be particularly useful during wafer inspection (block 12). Fig. 2 illustrates a perspective view of one embodiment of a rotating gripper wafer flipper apparatus 5 according to the present invention. Generally, the apparatus 5 includes a rotating gripper assembly which comprises a wafer holding structure 10 and a flipper shaft 20. The wafer holding structure 10 is mechanically coupled to the flipper shaft 20. The wafer holding structure 10 is configured to hold a disc-like substrate, such as a semiconductor wafer for inspection. Indeed, as apparent from the following discussion, the wafer holding structure 10 may be constructed so that it may hold semiconductor wafers of differing diameters.

In one embodiment, the flipper shaft 20 is connected to a motor assembly, discussed herein with reference to Fig. 4. The flipper shaft 20 may be connected to the motor assembly in any suitable manner, such as by a series of pulleys (not shown). The motor assembly provides a mechanism for flipping the wafer, at least 180° and advantageously 360°, about the flipper shaft 20. As the motor assembly rotates the flipper shaft 20, the wafer holding structure 10 and thus the wafer rotates about the flipper shaft 20.

Fig. 3 illustrates the apparatus 5, as shown in Fig. 2, with a semiconductor wafer 40 mounted on the wafer holding structure 10. Again, the wafer holding structure 10 is mechanically coupled to the flipper shaft 20 whose rotation is driven by the motor assembly.

As the motor assembly turns the flipper shaft 20 and the wafer holding structure 10, the semiconductor wafer 40 is permitted to rotate about the axis A-A. By rotating the semiconductor wafer 40 about the axis A-A, an operator inspecting the wafer 40 can examine the frontside and the backside of the semiconductor wafer 40 at any desired angle, without removing the semiconductor wafer 40 from the apparatus 5.

The semiconductor wafer 40 is held securely in place by a plurality of wedge assemblies 50 and 55. Here, the wafer holding structure 10 contains three wedge assemblies to hold the semiconductor wafer 40 securely in place as it rotates about the axis A-A. Each wedge assembly 50 and 55 contains a V-shaped slot in which the semiconductor wafer 40 can be deposited. The V-shaped slot in the wedge assembly 50 and 55 advantageously contains a rubber material, such as Tygon, to secure the semiconductor wafer 40 within each wedge assembly 50 and 55. Also, one wedge assembly, here the center wedge assembly 50 (hereinafter referred to as the "drive wheel wedge assembly 50"), may be coupled to a motor assembly (shown in Fig. 4), which rotates the drive wheel wedge assembly 50. Rotation of the drive wheel wedge assembly 50 causes the semiconductor wafer 40 to rotate about an axis B-B disposed generally perpendicular to the surface of the semiconductor wafer 40 and extending generally through the axial center of the semiconductor wafer 40. The remaining wedge assemblies 55 in this exemplary embodiment are idler wheel wedge assemblies 55 which freely rotate as the semiconductor wafer 40 is rotated by the drive wheel wedge assembly 50.

One embodiment of the motor assembly 30 is illustrated in Fig. 4. The motor assembly 30 may be comprised of two stepper motors, one to control the flipping and the other to control rotation of the wafer 40, as shown here. However, a single motor may be used to control both the flipping and rotation of the wafer 40. Any type of motor which may be configured to provide incremental, non-continuous rotation of a shaft, such as a brushless DC motor or a permanent magnet motor, may be used. In this embodiment, a pitch motor 22 is configured to turn the flipper shaft 20 to rotate the semiconductor wafer 40, 360° about the axis A-A (illustrated in Fig. 3). Flipper drive pulleys 23 and 24 may be driven by a motor belt 25 which operatively connects the pitch motor 22 to the flipper shaft 20. The rotational drive motor 26 permits rotation of the wafer 40 about the axis B-B (illustrated in Fig. 3). Rotational drive pulleys 27, 28, 29, and 31 are operatively connected between the rotational drive motor 56 and the rotational drive shaft (not shown) by motor drive belts 32 and 33.

While a motorized assembly to control the movement of the apparatus 5 has been described, it should be clear that a non-motorized flipper assembly may also be used. Instead of the flipper shaft 20 being coupled to a motor assembly 30, the flipper shaft 20 or the gripper arms 60 may have an appendage attached thereto, such as a handle (not shown), which will permit manual pitch movement of the wafer about the axis A-A. Also, a thumb wheel (not shown) may be present in the gripper arms 60 to permit rotation of the wafer generally about the axis B-B. In other words, virtually any mechanism which will permit rotation of the gripper arms 60 about the axis A-A and permit rotation of the wafer about the axis B-B may be used.

Figs. 5A-5C illustrate a flipping sequence as the wafer holding structure 10 is rotated about axis A-A (shown in Fig. 3). Fig. 5A illustrates the wafer holding structure 10 in a position in which the semiconductor wafer 40 is parallel to the ground. The frontside of the semiconductor wafer 40 having several dies formed thereon is face-up to allow an operator to inspect the frontside of the wafer 40. Fig. 5B illustrates the wafer holding structure 10 rotated approximately 45° from its initial position. This permits an operator to inspect the semiconductor wafer 40 at an angle to detect any anomalous particles or debris which may be on the surface of the semiconductor wafer 40. Fig. 5C illustrates the wafer holding structure 10 rotated 180° from its starting point. Here, the backside of the semiconductor wafer 40 is face up which permits operators to inspect the backside of the semiconductor wafer 40. While the figures 5A-5C illustrate the wafer holding structure 10 in three rotatable positions, it should be clear that an operator may rotate the wafer holding structure to any position, as permitted by the particular motors used in the apparatus 5, to facilitate inspection of the semiconductor wafer 40.

Fig. 6 illustrates a more detailed view of one embodiment of the wafer holding structure 10 and the flipper shaft 20. The wafer holding structure 10 is comprised of two gripper arms 60. Each gripper arm 60 comprises two idler wheel wedge assemblies 55. The wafer holding structure 10 also comprises a drive wheel wedge assembly 50. The drive wheel wedge assembly 50 contains a slot in which to deposit a semiconductor wafer (not shown). Likewise, the idler wheel wedge assemblies 55 also contain respective slots to hold a semiconductor wafer. A semiconductor wafer is placed on the extended flat portions of the wedge assemblies 50 and 55. With the semiconductor wafer resting on the extended flat

portions of the wedge assemblies 50 and 55, the gripper arms 60 are pulled together by tension springs 70. The tension springs 70 permit the gripper arms 60 to slide in a horizontal direction. The range of motion of the tension springs 70 may be advantageously limited by a stopping mechanism, such as a post, which insures that the gripper arms will only open wide enough to accommodate the largest wafers. As the tension springs 70 pull the gripper arms 60 together, the semiconductor wafer is forced upward along an incline area on the wedge assemblies 50 and 55 and into the wedge slots on the wedge assemblies 50 and 55. The pressure of the gripper arms 60 provided by the tension springs 70 and the slots in the wedge assemblies 50 and 55 work together to secure the semiconductor wafer within the wafer holding structure 10. The wedge assembly pockets contain a friction material, such as Tygon, to buffer the semiconductor wafer within the slots. Alternatively, the gripper arms 60 may be permitted to pivot about joints 65 which may also permit the opening and closing of the gripper arms to allow loading and unloading of the wafers.

A cross-sectional view of the wedge assembly 50 and 55 is illustrated in Fig. 6A. A wafer (not shown) is placed on the extended flat portion 51 of the wedge assembly 50 and 55. As the gripper arms (not shown) close about the perimeter of the wafer, the wafer is forced up the inclined portion 52 of the wedge assembly 50 and 55 and into the wedge slot 53. The wedge slot contains a friction material 54, such as Tygon, to secure the wafer within the wedge assembly 50 and 55. Bearings 56 and 57 will permit the wedge assembly 50 and 55 to rotate about the wedge shaft 58.

The drive wheel wedge assembly 50 may be coupled to a rotational drive motor (shown in Fig. 4) to provide rotation of the semiconductor wafer about an imaginary axis disposed generally perpendicular to the surface of the wafer and extending generally through the axial center of the wafer. The semiconductor wafer can be flipped by a motor belt turning the flipper drive pulley 80 which in turn rotates the hollow flipper shaft 20. A mounting head 90 locks the flipper shaft 20 to the wafer holding structure 10. Retraction mechanisms 100 may be used to prevent the gripper arms 60 of the wafer holding structure 10 from opening without the wafer being in an upright horizontal position. Once the gripper arms 60 rotate from an upright and horizontal starting position so that the retraction mechanisms 100 are pushed into a locked position within the housing of the apparatus 5. This insures that the semiconductor wafer will not accidentally be released from the wafer holding structure 10 during the inspection process. To remove the semiconductor wafer, the wafer holding structure 10 is rotated to the upright horizontal position, so that the retraction mechanisms 100 can be extended. The gripper arms 60 are opened so that the semiconductor wafer slides down the inclined portion of the wedge assemblies 50 and 55. The semiconductor wafer is then ready to be removed from the inspection apparatus 5.

As previously discussed, while the semiconductor wafer is captured by the wedge assemblies 50 and 55, it can also be rotated about an imaginary axis disposed generally perpendicular to the surface of the wafer and extending generally through the axial center of the wafer. The two idler wheel wedge assemblies 55 are forced inward by the tensioning springs 70. Since the idler wheel wedge assemblies 55 are advantageously off center of the semiconductor wafer, they force the semiconductor wafer into the drive wheel wedge

assembly 50. This tension provides enough friction on the drive wheel wedge assembly 55 so that the semiconductor wafer can be driven to rotate within the confines of the wedge assemblies 50 and 55. A rotational drive pulley 110 is driven by a motor drive belt connected to a rotational drive motor which turns the rotational drive shaft 120 which may be held inside the hollow flipper shaft 20. In this embodiment, the flipper shaft 20 is a hollow shaft with an axial opening extending therethrough. This rotational drive shaft 120 then rotates the drive wheel wedge assembly 50 to rotate the semiconductor wafer about an axis disposed generally perpendicular to the surface of the wafer and extending generally through the axial center of the wafer. The motors which are connected to the rotational drive pulley 110 and the flipper drive pulley 80 which provide for the rotation of the semiconductor wafer about axis A-A and axis B-B (shown in Fig. 3), may be controlled by operators using an electro-mechanical device, such as a roller ball or a joy stick.

Fig. 7 illustrates a partial cross-section of the rotating gripper wafer flipper apparatus 5 illustrated in Fig. 2, taken along line 7-7. This figure is intended to illustrate one embodiment of the mechanisms used to rotate the wafer along axis A-A and axis B-B, as illustrated in Fig. 3. Beginning first with the flipper shaft system, i.e., the mechanism responsible for rotating the semiconductor wafer about the axis A-A (illustrated in Fig. 3), the apparatus 5 comprises the flipper shaft 20 and the flipper drive pulley 80. The flipper shaft pulley 54 is coupled to the flipper shaft 20 which is connected to the wafer holding structure 10. A motor driven belt attached to the flipper drive pulley 80 permits rotation of the wafer holding structure 10 about the axis A-A.

One embodiment of the mechanisms used to rotate the semiconductor wafer about the axis B-B (shown in Fig. 3) include the rotational drive shaft 120 and the rotational shaft pulley 110. The rotational drive shaft 120 may be configured to fit inside the hollow flipper shaft 20. The rotational drive shaft 120 is held inside the hollow flipper shaft 20 by rotational shaft bearings 130 which press fit inside the flipper shaft 20. The rotational drive shaft 120 is coupled to the rotational drive pulley 110. The drive pulley 110 may be coupled to a rotational motor by a motor belt (not shown) which permits rotation of the rotational drive shaft 120. The rotational drive shaft 120 is coupled to a worm gear 140. The worm gear 140 is coupled to a worm driven gear 150 which drives the drive wheel wedge assembly 50 to rotate as the rotational drive shaft 120. Both the motors used to control the flipper shaft 20 and the rotational drive shaft 120 may be coupled to tools such as a joy stick or a roller ball, which may be controlled by an operator during the inspection process.

Fig. 8 illustrates a flow chart of the inspection process. First, the operator selects a wafer to be inspected, (Step 170). Next, an optical sensor in the inspection station checks the position of the wafer holding structure, (Step 172). That is to say, a sensor may be used to insure that the wafer holding structure is in an upright horizontal position such that it may receive a wafer. If the arms are not in an upright horizontal position, a wafer may not be loaded into the inspection system. If the arm position is upright and horizontal, a wafer can be loaded onto the wafer loading structure so that the wafer is placed on the lower flange of the wedge assemblies. The wafer may be loaded manually using a vacuum wand. (Step 174A). Alternately, a robotic arm proximately positioned next to the inspection station may be used to deposit the wafer onto the wafer holding structure. (Step 174B). Next, the gripper

arms are closed. (Step 176). As the retraction mechanisms are retracted, the wafer moves from the lower flange, up the inclined portion of the wedge assemblies, and into the v-shaped slots in the wedge assemblies. (Step 178). At this point, the arm position may be checked again. (Step 180). In one embodiment, the inspection apparatus contains an optical sensor
5 which is configured to locate a notch on the frontside of the wafer to begin the inspection process with the wafer in a predetermined position. Thus, the wafer may be rotated until the optical sensor senses a notch in the wafer. (Step 182). Next, the inspection of the wafer begins.

10 To inspect the wafer completely, the wafer may be rotated, plus or minus 360° for example, about an axis disposed generally perpendicular to the surface of the wafer and extending generally through the axial center of the wafer. The rotation of the wafer may be driven by operator input, using a joy stick, for example, to control the rotational motor. (Step 184). During the inspection process, an operator may inspect the wafer at various angles and
15 also inspect the backside of the wafer. Thus, the wafer may be rotated about the flipper shaft (illustrated in Figs. 2-7). The rotation of the wafer about the flipper shaft may be driven by operator input using a joy stick to control the pitch motor. (Step 186). Step 184 and Step 186 are iterated until the inspection of the wafer is complete, and the operator ends the wafer inspection. (Step 188).

20 The wafer is rotated to its upright horizontal position. (Step 190). The gripper arms are then opened. (Step 192) and the wafer slides down the inclined surfaces and on to the lower flanges of the wedge assemblies. (Step 194). At this point, the wafer is removed from

the wafer holding structure either manually, by use of a vacuum wand or similar apparatus for example (Step 196A), or automatically using a robot arm for example. (Step 196B). Finally, if there are more wafers to be inspected, the process returns to Step 172 and the inspection process can begin again. (Step 198). Otherwise, the inspection is complete.

5

While the invention may be susceptible to various modifications and alternative forms, specific embodiments have been shown by way of example in the drawings and have been described in detail, herein. However, it should be understood that the invention is not intended to be limited to the particular forms disclosed. Rather, the invention is to cover all
10 modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the following appended claims.

CLAIMS

What is claimed is:

1. An apparatus for inspecting a disc-like substrate comprising a holding
5 structure having members arranged to hold and rotate the substrate about a first axis, the holding structure being coupled to a rotatable member, the rotatable member configured to rotate the holding structure about a second axis different from the first axis.
- 10 2. The apparatus, as set forth in claim 1, wherein the members comprise a plurality of wedge assemblies configured to rotate the substrate about the first axis.
- 15 3. The apparatus, as set forth in claim 1, wherein the first axis is disposed generally perpendicular to a flat surface of the substrate and extends generally through an axial center of the substrate.
- 20 4. The apparatus, as set forth in claim 1, wherein the holding structure comprises two L-shaped gripping arms arranged to form a single U-shaped structure and configured to hold the substrate substantially parallel to the gripping arms.

5. The apparatus, as set forth in claim 4, wherein the U-shaped structure is configured to open and close about the perimeter of the substrate.

5 6. The apparatus, as set forth in claim 5, further comprising tensioning springs configured to permit the U-shaped structure to open and close about the perimeter of the substrate.

10 7. The apparatus, as set forth in claim 2, wherein the holding structure comprises three wedge assemblies, at least one wedge assembly coupled to a motor and configured to rotate the substrate about the first axis disposed generally perpendicular to a flat surface of the substrate and extending generally through an axial center of the substrate.

15

8. A method of inspecting a semiconductor wafer comprising the acts of:

(a) loading the substrate into a holding structure, the substrate having a first surface and a second surface;

20

(b) inspecting the first surface of the substrate by rotating the substrate within the holding structure about a first axis, the first axis disposed

generally perpendicular to the surface of the substrate and extending
generally through the axial center of the substrate;

5 (c) rotating the holding structure about a rotatable member to rotate the
substrate approximately 180° about a second axis, the rotatable
member being mechanically coupled to the holding structure;

(d) inspecting the second surface of the substrate; and

10 (e) removing the substrate from the holding structure.

9. The method as set forth in claim 8, wherein act (a) further comprises the acts

of:

15

(a) opening gripper arms of the holding structure;

(b) inserting the substrate into a wedge assembly on the gripper arms;

20 (c) retracting the wedge assembly; and

(d) closing the gripper arms.

10. The method, as set forth in claim 8, wherein act (b) comprises the act of rotating the substrate within the holding structure until a notch on the first surface of the substrate is optically sensed.

5

11. The method, as set forth in claim 8 wherein act (b) comprises the act of rotating the substrate within the holding structure by using a drive wheel wedge assembly mechanically coupled to a rotational drive motor, the drive wheel wedge assembly being coupled to the substrate.

10

12. The method, as set forth in claim 11, comprising controlling the rotation of the substrate by using an operator driven mechanism coupled to control the rotational drive motor.

15

13. The method, as set forth in claim 8, wherein act (c) comprises the act of rotating the holding structure about a rotatable member by using a pitch motor, the pitch motor being operably coupled to the rotatable member.

20

14. The method, as set forth in claim 13, comprising controlling the rotation of the substrate by using an operator driven mechanism coupled to control the pitch motor.

15. A method of fabricating an integrated circuit package comprising the acts of:

(a) disposing a plurality of integrated circuit devices onto a silicon wafer;

5 (b) inspecting the wafer by:

(1) loading the wafer into a wafer holding structure, the wafer having
a first surface and a second surface;

10 (2) inspecting the first surface of the wafer by rotating the wafer
within the wafer holding structure about a first axis, the first
axis disposed generally perpendicular to the surface of the
wafer and extending generally through the axial center of the
wafer;

15 (3) rotating the wafer holding structure about a rotatable member to
rotate the wafer approximately 180° about a second axis, the
rotatable member being mechanically coupled to the wafer
holding structure;

20 (4) inspecting the second surface of the wafer; and

(5) removing the wafer from the wafer holding structure.

(c) electrically testing the integrated circuit devices;

(d) singulating the integrated circuit devices; and

5

(e) packaging selected singulated integrated circuit devices to form
respective integrated circuit packages.

10

16. The method as set forth in claim 15, wherein act (b)(1) comprises the acts of:

(a) opening gripper arms of the wafer holding structure;

(b) inserting the wafer into a wedge assembly on the gripper arms;

15

(c) retracting the wedge assembly; and

(d) closing the gripper arms.

20

17. The method, as set forth in claim 15, wherein act (b)(2) comprises the act of
rotating the wafer within the wafer holding structure until a notch on the first surface of the
wafer is optically sensed.

18. The method, as set forth in claim 15, wherein act (b)(2) comprises the act of rotating the wafer within the wafer holding structure by using a wedge assembly mechanically coupled to a drive motor, the wedge assembly being coupled to the wafer.

5

19. The method, as set forth in claim 18, comprising controlling the rotation of the wafer by using an operator driven joystick coupled to control the drive motor.

10

20. The method, as set forth in claim 15, wherein act (b)(3) comprises the act of rotating the wafer holding structure about a rotatable member by using a pitch motor, the pitch motor being operably coupled to the rotatable member.

15

21. The method, as set forth in claim 20, comprising controlling the rotation of the wafer by using an operator driven joystick coupled to control the pitch motor.

ABSTRACT OF THE DISCLOSURE

5 A method and apparatus for inspecting semiconductor wafers. Specifically, an arm which is constructed to hold a wafer, is mounted on a rotational device to provide a user with the means of inspecting a wafer in any position without having to physically touch the wafer or move the wafer to another inspection station. The arm provides rotation about an axis parallel to the surface of the wafer, as well as rotation about an axis run which is perpendicular to the surface of the wafer and extends through the axial center of the wafer.

FIG. 1





FIG. 2






FIG. 4





FIG. 5A

FIG. 5C







FIG. 7




FIG. 8A





FIG. 8B



DECLARATION

As the below named inventors, we hereby declare that:

Our residence, post office address and citizenship are as stated below next to our names.

We believe we are the original, first and joint inventors of the subject matter which is claimed and for which a patent is sought on the invention entitled "**ROTATING GRIPPER WAFER FLIPPER**," the specification of which:

 X is attached hereto.
 Was filed on as Application Serial No.:

We hereby state that we have reviewed and understand the contents of the above identified specification, including the claims.

We acknowledge the duty to disclose to the Patent and Trademark Office all information known to us to be material to patentability of the subject matter claimed in this application, as "materiality" is defined in Title 37, Code of Federal Regulations, § 1.56.

We hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

PRIOR FOREIGN APPLICATION(S)

			<u>Priority Claimed</u>
(Number)	(Country)	(Date Filed)	Yes/No
(Number)	(Country)	(Date Filed)	Yes/No

We hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, we acknowledge the duty to disclose all information known to us to be material to patentability of the subject matter claimed in this application, as "materiality" is defined in Title 37, Code of Federal Regulations, § 1.56, which become available between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)	(Filing Date)	(Status)
--------------------------	---------------	----------

We hereby direct that all correspondence and telephone calls be addressed to Michael G. Fletcher, Fletcher, Yoder & Van Someren, P.O. Box 692289, Houston, Texas 77269-2289, (281) 970-4545.

We hereby declare that all statements made of our own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Inventor's Full Name: Willard L. Hofer
(First) (Initial) (Last)

Inventor's Signature: Willard L. Hofer

Date: 6/5/2000 Country of Citizenship U.S.A.

Residence Address: 469 S. Emily
(Include number, street name, city, state, and country)
Boise, Idaho 83709 U.S.A.

Post Office Address: _____
(If different) _____

Inventor's Full Name: Shawn D. Davis
(First) (Initial) (Last)

Inventor's Signature: Shawn Davis

Date: 6-5-2000 Country of Citizenship U.S.A.

Residence Address: 3023 W. Val Vista Ct.
(Include number, street name, city, state, and country)
Meridian, Idaho 83706 U.S.A.

Post Office Address: _____
(If different) _____

Post Office Address: _____
(If different) _____

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:	§	
Willard Lloyd Hofer et al.	§	Group Art Unit: Unassigned
	§	
Serial No.: Unassigned	§	
	§	Examiner: Unassigned
Filed: Herewith	§	
	§	
For: ROTATING GRIPPER WAFER FLIPPER	§	Atty Docket: MICS:0053/FLE
	§	99-0326

**ELECTION UNDER 37 C.F.R. §§ 3.71 AND 3.73
AND POWER OF ATTORNEY**

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

The undersigned, being Assignee of the entire interest in the above-identified application by virtue of an Assignment recorded in the United States Patent and Trademark Office as set forth below, hereby elects, under 37 C.F.R. § 3.71, to prosecute the application to the exclusion of the inventor(s).

The Assignee hereby revokes any previous Powers of Attorney and appoints:

Michael L. Lynch, Reg. No. 30,871; and Lia Pappas Dennison, Reg. No. 34,095

of MICRON TECHNOLOGY, INC.; and also

Michael G. Fletcher, Reg. No. 32,777, Patrick S. Yoder, Reg. No. 37,479,
Robert A. Van Someren, Reg. No. 36,038; and Diana M. Sangalli, Reg. No. 40,798

with the law firm of FLETCHER, YODER & VAN SOMEREN, as its attorneys with full power of substitution and revocation, to prosecute the application, to make alterations and amendments therein, to transact all business in the Patent and Trademark Office in connection therewith, to receive any Letters Patent, and for one year after issuance of such Letters Patent to file any request for a certificate of correction that may be deemed appropriate.

Pursuant to 37 C.F.R. § 3.73, the undersigned has reviewed the evidentiary documents, specifically the Assignment to MICRON TECHNOLOGY, INC. referenced below, and certifies that to the best of my knowledge and belief, title remains in the name of the Assignee.

Please direct all communications as follows:

Michael G. Fletcher
FLETCHER, YODER & VAN SOMEREN
P.O. Box 692289
Houston, TX 77269-2289
(281) 970-4545

ASSIGNEE. Micron Technology, Inc.

Date: 6-7-00

By: [Signature]
Name: Michael L. Lynch, Chief Patent Counsel

ASSIGNMENT

☒ Enclosed for recording
☐ Previously recorded.

Date:
Reel:
Frame: